

DPM 6133  
Base

DESOTO, INC.  
MATERIAL SAFETY DATA SHEET  
FOR COATINGS, RESINS, AND RELATED MATERIALS  
(APPROVED BY US DEPARTMENT OF LABOR "ESSENTIALLY SIMILAR" TO FORM OSHA-209)  
SECTION I

DESOTO, INC.  
ADMINISTRATIVE AND RESEARCH CENTER  
EMERGENCY TELEPHONE (312) 391-9000

1700 S. MT. PROSPECT ROAD  
DES PLAINES, ILLINOIS 60018

PRODUCT CLASS EPOXY  
TRADE NAME EPOXY PA COMPLIANCE PRIMER  
MANUFACTURERS CODE IDENTIFICATION 513X395  
DATE OF PREPARATION 11/21/84

\*\*\*\*\* SECTION II-HAZARDOUS INGREDIENTS \*\*\*\*\*

INGREDIENT	% BY*		TLV	MG/CU.M	VAPOR	
	WEIGHT	PPM			LEL	PRESSURE @ 20 DEG C
TALC NON ASBESTIFORM	15.0	20MPPCF			NA	NA
METHYL ETHYL KETONE	< 5.0	200		590	1.8	70
METHYL N-AMYL KETONE	10.0	50		235	1.1	2.1
1,1,1-TRICHLOROETHANE	30.0	350		1900	7	100

\* PERCENT BY WEIGHT:  
TO NEAREST 5%, PLUS OR MINUS 5%, FOR SUBSTANCES 5-95%;  
<5.0 FOR SUBSTANCES 0.5-5.0%;  
<0.5 FOR SUBSTANCES 0.0-0.5%.



NE = NOT ESTABLISHED  
NA = NOT APPLICABLE

\*\*\*\*\* SECTION III-PHYSICAL DATA \*\*\*\*\*

PROPERTY	MEASUREMENT
BOILING RANGE	165.0 TO 300.0 DEG F. 74.0 TO 149.0 DEG C. @ 760 MM HG
VAPOR DENSITY	X HEAVIER LIGHTER THAN AIR
WEIGHT PER GALLON	12.2 LBS.
PERCENT VOLATILE BY VOLUME	59.3
EVAPORATION RATE	FASTER X SLOWER THAN ETHER

11/21/84

## \*\*\*\*\* SECTION IV-FIRE AND EXPLOSION DATA \*\*\*\*\*

DOT CATEGORY      FLAMMABLE LIQUID      FLASH POINT      61.0 DEG F.  
OSHA CATEGORY      FLAMMABLE LIQUID-CLASS I B      (CLOSED CUP)      16.1 DEG C.

LOWER EXPLOSIVE LIMIT      SEE II

EXTINGUISHING MEDIA: USE NATIONAL FIRE PROTECTION ASSOCIATION CLASS B  
EXTINGUISHERS (CARBON DIOXIDE, DRY CHEMICAL OR FOAM).

UNUSUAL FIRE AND EXPLOSION HAZARDS: KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO HOT SURFACES.  
SPECIAL FIRE FIGHTING PROCEDURES: WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTO IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WEAR NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN AND EYES.

## \*\*\*\*\* SECTION V-HEALTH HAZARD DATA \*\*\*\*\*

THRESHOLD LIMIT VALUE: SEE II (NOT ESTABLISHED FOR PRODUCT)

## EFFECTS OF OVEREXPOSURE:

INHALATION: ANESTHETIC. IRRITATION OF THE RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS OR COMA.

SKIN OR EYE CONTACT: PRIMARY IRRITATION.

EMERGENCY AND FIRST AID PROCEDURES: INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. NOTIFY A PHYSICIAN. SKIN CONTACT: WASH AFFECTED AREAS WITH WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN. EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES. CONSULT A PHYSICIAN. INGESTION: CONSULT A PHYSICIAN.

## \*\*\*\*\* SECTION VI-REACTIVITY DATA \*\*\*\*\*

STABILITY:                      UNSTABLE      X      STABLE

INCOMPATIBILITY (MATERIALS TO AVOID):

SLOW HYDROLYSIS MAY EVENTUALLY PRODUCE CORROSIVE ACID.

HAZARDOUS DECOMPOSITION PRODUCTS: PRODUCTS OF COMBUSTION ARE HAZARDOUS. MAY INCLUDE HYDROGEN CHLORIDE AND POSSIBLY SMALL AMOUNTS OF PHOSGENE AND CHLORINE.

HAZARDOUS POLYMERIZATION:                      MAY OCCUR      X WILL NOT OCCUR

CONDITIONS TO AVOID:

11/21/84

## \*\*\*\*\* SECTION VII-SPILL OR LEAK PROCEDURES\*\*\*\*\*

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

WASTE DISPOSAL METHODS: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

## \*\*\*\*\*SECTION VIII-SPECIAL PROTECTION INFORMATION\*\*\*\*\*

## RESPIRATORY PROTECTION:

IF EXPOSURE EXCEEDS OCCUPATIONAL EXPOSURE LIMITS INDICATED IN SECTION II USE NIOSH/MSHA APPROVED ORGANIC VAPOR RESPIRATOR. IN CONFINED AREAS USE NIOSH/MSHA APPROVED AIR LINE TYPE RESPIRATORS OR HOODS.

VENTILATION: WHERE EMPLOYEES MAY BE EXPOSED, PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP LEVEL OF HAZARDOUS INGREDIENTS IN SECTION II BELOW RECOMMENDED (ACGIH) OR REGULATED (OSHA) LIMIT. WHERE EMPLOYEES WILL NOT BE EXPOSED, KEEP LEL IN SECTION II BELOW 25% OF LIMIT.

PROTECTIVE GLOVES:       X   RECOMMENDED               REQUIRED

EYE PROTECTION: USE SAFETY EYEWARE DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

OTHER PROTECTIVE EQUIPMENT: AVOID SKIN CONTACT BY USE OF OTHER PROTECTIVE CLOTHING. A SAFETY SHOWER, AN EYE BATH AND WASHING FACILITIES SHOULD BE AVAILABLE.

## \*\*\*\*\* SECTION IX-SPECIAL PRECAUTIONS\*\*\*\*\*

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF FLAMMABLE LIQUIDS.

OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.

CONTACT BETWEEN 1,1,1-TRICHLOROETHANE AND LIQUID HANDLING EQUIPMENT CONSTRUCTED OF ALUMINUM MAY CAUSE AN EXPLOSIVE REACTION. CONSULT EQUIPMENT SUPPLIER TO BE CERTAIN THAT THE EQUIPMENT USED TO HANDLE THIS MATERIAL IS COMPATIBLE WITH 1,1,1-TRICHLOROETHANE.

VAPORS OF THIS PRODUCT ARE HEAVIER THAN AIR AND MAY COLLECT IN LOW OR CONFINED AREAS. DO NOT ENTER SUCH AREAS WITHOUT FOLLOWING APPROPRIATE PROCEDURES INCLUDING AIR MONITORING, USE OF SUPPLIED AIR IF NECESSARY AND THE PRESENCE OF AN OBSERVER FOR ASSISTANCE.

DO NOT SAND, FLAME CUT, BRAZE OR WELD THE DRY COATING WITHOUT NIOSH APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.

OBSERVE PRECAUTIONARY LABEL WARNINGS.

PREPARED BY S. M. STEVENSON

BOE-C6-0225548